

Outdoor LED Sign



Feature



Wifi transmission is convenient and fast, saving costs in all aspects.

You can also add 4G module to update the playback content anytime and anywhere.

Cascade control can be performed, one device controls multiple different led screens at the same time, and the playback content is updated synchronously with one click.

Feature



High brightness. The brightness can reach up to 6000, and the image can be clearly seen even in direct sunlight outdoors.

Good waterproof performance. Waterproof grade IP65, with rear cover and waterproof eaves for double protection.



Modular design. When part of screen is damaged, just replace part of led module and it can be used normally, which is easy to maintain.

It can be fully customized according to the actual situation to achieve the best display and marketing effect.

Specification Parameter

Model	P2.5	P4	P5	P6	P8
Module Size(mm)	320x160			192x192	320x160
Scanning	1/16	1/10	1/8	1/8	1/5
Cabinet Size(mm)	Customized				
Density(dot/m ²)	160000	62500	40000	27777	15625
Brightness(cd/m ²)	4000-6000				
Max. Power(w/m ²)	1400				
Ave. Power(w/m ²)	700				
Cabinet Material	Iron/ Aluminum				
Refresh Rate(hz)	1920-3840				
Viewing Angle	H: 160°; V: 160°				
Input Voltage	AC100-240V 50/60Hz				
IP Rate	IP65				
Temperature-operating	-10°C-50°C				
Humidity-operating	10%-90%				

Product case

